



**REF. I1 - ISSUE NO.1**

**13 Feb 07**

---

**Safety Data Sheet**

**John L. Lord & Son (Rizistal) Ltd**

---

**1. Identification of Substance/Preparation and Company Name**

**RIZISTALCRETE**

John L. Lord & Son (Rizistal) Limited  
Wellington Cement Works, Ainsworth Road, Bury. BL8 2RS  
Tel: 0161 764 4617 (Out of Office Hours: 0161 763 9315/07976 745513).

---

**2. Composition / Information on Ingredients**

47% Carboxylated styrene butadiene polymer.  
53% Water.

R10	Flammable
R20	Harmful by inhalation
R36/38	Irritating to eyes and skin

---

**3. Hazards Identification**

This liquid is not considered hazardous under legislation. Vapour might cause dizziness. Prolonged contact with skin or eyes can cause irritation.

---

**4. First Aid Measures**

<u>Entry Route</u>	<u>Symptoms</u>	<u>Treatment</u>
Inhalation	Dizziness unlikely.	Remove to fresh air and seek medical help if dizziness persist.
Skin Contact	Irritation.	Remove contaminated clothing. Wash affected skin thoroughly with soap and water.

Eye Contact	Irritation.	Irrigate eye thoroughly with plenty of water for at least 10 minutes. Seek medical advice should symptoms persist.
Ingestion	Unlikely to occur.	Seek medical advice immediately.

---

## 5. Fire-Fighting Measures

This is a non-flammable aqueous dispersion. Use extinguisher commensurate with surrounding material.

---

## 6. Accidental Release Measures

Personal Protection	Ensure good ventilation. Protect skin and eyes.
Environmental Precautions	Do not allow product to enter drains or water courses.
Cleaning Up	Absorb into sand or similar material and then contain this.

---

## 7. Handling and Storage

Handling	Keep in its closed containers until poured for use.
Storage	Keep in its closed containers and store in cool, dry conditions. Keep away from aluminium, copper and their alloys.

---

## 8. Workplace Exposure Limits Controls / Personal Protection

Workplace Exposure Limits

	8 Hrs	15 mins
Styrene	100PPM 430 mg/m <sup>-3</sup>	250PPM 1080mg/m <sup>-3</sup>



**12. Ecological Information**

To be considered hazardous to the environment and to be kept from water courses, waste water or soil.

---

**13. Disposal Considerations**

Product to be treated as Hazardous Waste and disposed of accordingly.

---

**14. Transport Information**

Not classified as dangerous for transport.

---

**15. Regulatory Information**

R10	Flammable	
	R20	Harmful by inhalation
	R36/38	Irritating to eyes and skin

None, but the product should be considered when making assessments under the UK Control of Substances Hazardous to Health regulations – COSHH.

---

**16. Other Information**

The product should only be used as described in the document “COSHH Assessment” issued by John L. Lord & Son (Rizistal) Ltd.