



**REF. I2 - ISSUE NO.1**

**13 Feb 07**

---

**Safety Data Sheet**

**John L. Lord & Son (Rizistal) Ltd**

---

**1. Identification of Substance/Preparation and Company Name**

**RIZISTALCRETE - CEMENT**

John L. Lord & Son (Rizistal) Limited  
Wellington Cement Works, Ainsworth Road, Bury. BL8 2RS  
Tel: 0161 764 4617 (Out of Office Hours: 0161 763 9315/07976 745513).

---

**2. Composition / Information on Ingredients**

Ordinary Portland cement.

---

**3. Hazards Identification**

In contact with water (including tears and sweat) cement becomes strongly alkaline able to cause burns and ulcers. As nerve endings may be damaged, burning may not be felt! Less severely, irritant dermatitis may occur. Allergic dermatitis, from Hexavalent chromium salts, is also possible.

---

**4. First Aid Measures**

<u>Entry Route</u>	<u>Symptoms</u>	<u>Treatment</u>
Inhalation	Irritation then inflammation of passages.	Remove to fresh air and seek medical help should condition persist.
Skin Contact	Irritation; pain, ulcers Beware damaged nerve Endings giving no pain!	Remove contaminated clothing. Wash affected skin thoroughly with soap and water.
Eye Contact	Irritation; pain.	Irrigate eye thoroughly with plenty of water for at least 10 minutes. Seek medical advice

should symptoms persist.

Ingestion	Unlikely to occur.	Wash out mouth with water. Give plenty of water to drink.
-----------	--------------------	--

---

## 5. Fire-Fighting Measures

This is a non-flammable aqueous dispersion. Use extinguisher commensurate with surrounding material.

---

## 6. Accidental Release Measures

Personal Protection	Ensure good ventilation. Protect skin and eyes. If product has become wet also protect feet.
Environmental Precautions	Do not allow product to enter drains or water courses.
Cleaning Up	If dry vacuum or sweep up (minimising dust generation and place in dry containers. If wet the product will subsequently set hard.

---

## 7. Handling and Storage

Handling	Keep in its closed bags until poured for use.
Storage	Keep in its closed bags and store in dry conditions.

---

## 8. Workplace Exposure Controls / Personal Protection

Workplace Exposure Limits	8 Hrs	15 mins
Total inhalation dust	10mg.m <sup>-3</sup>	
Respirable dust.	4mg.m <sup>-3</sup>	
Protection	Respiratory	Not required in normal use. Dust mask if dust is generated.
Measures	Hand	Impermeable gloves; beware dust inside gloves!
	Eye	Goggles.



**14. Transport Information**

Not classified as dangerous for transport.

---

**15. Regulatory Information**

None, but the product should be considered when making assessments under the UK Control of Substances Hazardous to Health regulations – COSHH.

---

**16. Other Information**

The product should only be used as described in the document “COSHH Assessment” issued by John L. Lord & Son (Rizistal) Ltd.