

SAFETY DATA SHEET

EPIGARD ES100 FLOOR GRADE PRIMER - BASE COMPONENT (PART A)

Page 1

Issued: 24/10/2008

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPIGARD ES100 FLOOR GRADE PRIMER - BASE COMPONENT (PART A)

Product code: 02/01/PB

Company name: John L Lord & Son Ltd.

Ainsworth Road

Bury

Lancashire

BL8 2RS

United Kingdom

Tel: +44 (0)161 764 4617

Fax: +44 (0)161 763 1873

Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BISPHENOL F EPOXY RESIN 50-70%

CAS: 55492-52-9

[Xi] R36/38; [Sens.] R43; [N] R51/53

- BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} 10-30%

EINECS: 500-033-5 CAS: 25068-38-6

[Xi] R36/38; [Sens.] R43; [N] R51/53

- C13/C15 ALKYLGLYCIDYLETHER 10-30%

EINECS: 268-358-2 CAS: 68081-84-5

[Xi] R36/38; [Sens.] R43; [N] R51/53

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

[cont...]

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.
Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to eyes and skin.

Sensitisation: May cause sensitisation by skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.
Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 3082

ADR Class: 9

Packing group: III

Classification code: M6

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL F EPOXY RESIN)

Labelling: 9

Hazard ID no: 90



IMDG / IMO

UN no: 3082	Class: 9
Packing group: III	EmS: F-A,S-F
Marine pollutant: .	Labelling: 9

IATA / ICAO

UN no: 3082	Class: 9
Packing group: III	Packing instructions: 914
Labelling: 9	

15. REGULATORY INFORMATION

Hazard symbols: Irritant.
Dangerous for the environment.



Risk phrases: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S24: Avoid contact with skin.
S37: Wear suitable gloves.
S60: This material and its container must be disposed of as hazardous waste.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Haz. ingredients (label): BISPHENOL F EPOXY RESIN; BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}; C13/C15 ALKYLGLYCIDYLETHER

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.

SAFETY DATA SHEET
EPIGARD ES100 FLOOR GRADE PRIMER - BASE COMPONENT (PART A)

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPIGARD ES100 FLOOR GRADE PRIMER - HARDENER COMPONENT (PART B)

Product code: 02/01/PH

Company name: John L Lord & Son Ltd.

Ainsworth Road

Bury

Lancashire

BL8 2RS

United Kingdom

Tel: +44 (0)161 764 4617

Fax: +44 (0)161 763 1873

Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation, in contact with skin and if swallowed. Causes burns.
May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BENZYL ALCOHOL 50-70%

EINECS: 202-859-9 CAS: 100-51-6

[Xn] R20/22

- 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE 30-50%

EINECS: 220-666-8 CAS: 2855-13-2

[Xn] R21/22; [C] R34; [Sens.] R43; [-] R52/53

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Harmful by inhalation, in contact with skin and if swallowed. Causes burns.

Sensitisation: May cause sensitisation by skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2289

ADR Class: 8

Packing group: III

Classification code: C7

Shipping name: ISOPHORONEDIAMINE

Labelling: 8

Hazard ID no: 80

**IMDG / IMO**

UN no: 2289

Class: 8

Packing group: III
Marine pollutant: NO

EmS: F-A,S-B
Labelling: 8

IATA / ICAO

UN no: 2289
Packing group: III
Labelling: 8

Class: 8
Packing instructions: 818(P&CA); 820(CAO)

15. REGULATORY INFORMATION

Hazard symbols: Corrosive.



Risk phrases: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R34: Causes burns.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S60: This material and its container must be disposed of as hazardous waste.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Haz. ingredients (label): BENZYL ALCOHOL; 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R20/22: Harmful by inhalation and if swallowed.

SAFETY DATA SHEET
EPIGARD ES100 FLOOR GRADE PRIMER - HARDENER COMPONENT (PART B)

R21/22: Harmful in contact with skin and if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET

EPIGARD ES100 FLOOR GRADE - BASE COMPONENT (PART A)

Page 1

Issued: 24/10/2008

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPIGARD ES100 FLOOR GRADE - BASE COMPONENT (PART A)

Product code: 02/01/FGA

Company name: John L Lord & Son Ltd.

Ainsworth Road

Bury

Lancashire

BL8 2RS

United Kingdom

Tel: +44 (0)161 764 4617

Fax: +44 (0)161 763 1873

Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BISPHENOL F EPOXY RESIN 50-70%

CAS: 55492-52-9

[Xi] R36/38; [Sens.] R43; [N] R51/53

- BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT} 10-30%

EINECS: 500-033-5 CAS: 25068-38-6

[Xi] R36/38; [Sens.] R43; [N] R51/53

- C13/C15 ALKYLGLYCIDYLETHER 10-30%

EINECS: 268-358-2 CAS: 68081-84-5

[Xi] R36/38; [Sens.] R43; [N] R51/53

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.
Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to eyes and skin.

Sensitisation: May cause sensitisation by skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.
Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 3082

ADR Class: 9

Packing group: III

Classification code: M6

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL F EPOXY RESIN)

Labelling: 9

Hazard ID no: 90



IMDG / IMO

UN no: 3082	Class: 9
Packing group: III	EmS: F-A,S-F
Marine pollutant: .	Labelling: 9

IATA / ICAO

UN no: 3082	Class: 9
Packing group: III	Packing instructions: 914
Labelling: 9	

15. REGULATORY INFORMATION**Hazard symbols:** Irritant.

Dangerous for the environment.



Risk phrases: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S24: Avoid contact with skin.
S60: This material and its container must be disposed of as hazardous waste.
S37: Wear suitable gloves.
S60: This material and its container must be disposed of as hazardous waste.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Haz. ingredients (label): BISPHENOL F EPOXY RESIN; BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}; C13/C15 ALKYLGLYCIDYLETHER

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R36/38: Irritating to eyes and skin.

SAFETY DATA SHEET
EPIGARD ES100 FLOOR GRADE - BASE COMPONENT (PART A)

R43: May cause sensitisation by skin contact.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET

EPIGARD ES100 FLOOR GRADE - HARDENER COMPONENT (PART B)

Page 1

Issued: 24/10/2008

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPIGARD ES100 FLOOR GRADE - HARDENER COMPONENT (PART B)

Product code: 02/01/FGB

Company name: John L Lord & Son Ltd.

Ainsworth Road

Bury

Lancashire

BL8 2RS

United Kingdom

Tel: +44 (0)161 764 4617

Fax: +44 (0)161 763 1873

Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation, in contact with skin and if swallowed. Causes burns.
May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BENZYL ALCOHOL 50-70%

EINECS: 202-859-9 CAS: 100-51-6

[Xn] R20/22

- 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE 30-50%

EINECS: 220-666-8 CAS: 2855-13-2

[Xn] R21/22; [C] R34; [Sens.] R43; [-] R52/53

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

[cont...]

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Pale yellow

Odour: Characteristic odour

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Harmful by inhalation, in contact with skin and if swallowed. Causes burns.

Sensitisation: May cause sensitisation by skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: Bioaccumulation potential.

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 2289

ADR Class: 8

Packing group: III

Classification code: C7

Shipping name: ISOPHORONEDIAMINE

Labelling: 8

Hazard ID no: 80

**IMDG / IMO**

UN no: 2289

Class: 8

Packing group: III
Marine pollutant: NO

EmS: F-A,S-B
Labelling: 8

IATA / ICAO

UN no: 2289 **Class:** 8
Packing group: III **Packing instructions:** 818(P&CA); 820(CAO)
Labelling: 8

15. REGULATORY INFORMATION

Hazard symbols: Corrosive.



Risk phrases: R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
 R34: Causes burns.
 R43: May cause sensitisation by skin contact.
 R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
 S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 S60: This material and its container must be disposed of as hazardous waste.
 S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Haz. ingredients (label): BENZYL ALCOHOL; 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R20/22: Harmful by inhalation and if swallowed.

SAFETY DATA SHEET
EPIGARD ES100 FLOOR GRADE - HARDENER COMPONENT (PART B)

R21/22: Harmful in contact with skin and if swallowed.

R34: Causes burns.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

SAFETY DATA SHEET

EPIGARD ES100 FLOOR GRADE - AGGREGATE COMPONENT (PART C)

Page 1

Issued: 24/10/2008

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: EPIGARD ES100 FLOOR GRADE - AGGREGATE COMPONENT (PART C)

Product code: 02/01/FGC

Company name: John L Lord & Son Ltd.

Ainsworth Road

Bury

Lancashire

BL8 2RS

United Kingdom

Tel: +44 (0)161 764 4617

Fax: +44 (0)161 763 1873

Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to respiratory system.

Workplace exposure limit: This substance does not have a workplace exposure limit.

PBT: This substance is not identified as a PBT substance.

Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: CRYSTALLINE SILICA >90%
[Xi] R37

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not create dust.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of dust in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Powder

Colour: Various

Odour: Odourless

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to respiratory system.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.
Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R37: Irritating to respiratory system.

Safety phrases: S22: Do not breathe dust.

Haz. ingredients (label): CRYSTALLINE SILICA

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R37: Irritating to respiratory system.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.