

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: URAGARD HT 110W - BASE COMPONENT (PART A)
Product code: 03/01/110B
Company name: John L Lord & Son Ltd.
Ainsworth Road
Bury
Lancashire
BL8 2RS
United Kingdom
Tel: +44 (0)161 764 4617
Fax: +44 (0)161 763 1873
Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation and in contact with skin.
Workplace exposure limit: This substance does not have a workplace exposure limit.
PBT: This substance is not identified as a PBT substance.
Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: 1,4-BUTANE DIOL 1-10%
CAS: 110-63-4
[Xn] R22

- XYLENE 10-30%
EINECS: 215-535-7 CAS: 1330-20-7
[-] R10; [Xn] R20/21; [Xi] R38

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: XYLENE
UK - 8 hour TWA: 220 mg/m³
UK - 15 min. STEL: 441 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: White

Odour: Characteristic odour

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Harmful by inhalation and in contact with skin.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 3082

ADR Class: 9

Packing group: III

Classification code: M6

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (XYLENE)

Labelling: 9

Hazard ID no: 90



IMDG / IMO

UN no: 3082	Class: 9
Packing group: III	EmS: F-A,S-F
Marine pollutant: .	Labelling: 9

IATA / ICAO

UN no: 3082	Class: 9
Packing group: III	Packing instructions: 914
Labelling: 9	

15. REGULATORY INFORMATION**Hazard symbols:** Harmful.**Risk phrases:** R20/21: Harmful by inhalation and in contact with skin.**Safety phrases:** S36/37: Wear suitable protective clothing and gloves.

S60: This material and its container must be disposed of as hazardous waste.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R22: Harmful if swallowed.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: URAGARD HT 110W - HARDENER COMPONENT (PART B)
Product code: 03/01/110H
Company name: John L Lord & Son Ltd.
Ainsworth Road
Bury
Lancashire
BL8 2RS
United Kingdom
Tel: +44 (0)161 764 4617
Fax: +44 (0)161 763 1873
Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.
Workplace exposure limit: This substance does not have a workplace exposure limit.
PBT: This substance is not identified as a PBT substance.
Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIPHENYLMETHANE-2,2'-DI-ISOCYANATE >90%
EINECS: 219-799-4 CAS: 2536-05-2
[Xn] R20; [Xi] R36/37/38; [Sens.] R42/43
Contains: ISOCYANATES

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: DIPHENYLMETHANE-2,2'-DI-ISOCYANATE

UK - 8 hour TWA: 0.02 mg/m³

UK - 15 min. STEL: 0.07 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Brown

Odour: Earthy, musty.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Harmful by inhalation. Irritating to eyes, respiratory system and skin.

Sensitisation: May cause sensitisation by inhalation and skin contact.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.
Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R20: Harmful by inhalation.

SAFETY DATA SHEET
URAGARD HT 110W - HARDENER COMPONENT (PART B)

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitisation by inhalation and skin contact.

Safety phrases: S23: Do not breathe fumes.

S24: Avoid contact with skin.

S37: Wear suitable gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S60: This material and its container must be disposed of as hazardous waste.

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

Precautionary phrases: Contains isocyanates. See information supplied by the manufacturer.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R20: Harmful by inhalation.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitisation by inhalation and skin contact.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: URAGARD HT 110W - AGGREGATE COMPONENT (PART C)
Product code: 03/01/110W
Company name: John L Lord & Son Ltd.
Ainsworth Road
Bury
Lancashire
BL8 2RS
United Kingdom
Tel: +44 (0)161 764 4617
Fax: +44 (0)161 763 1873
Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Irritating to respiratory system. Risk of serious damage to eyes.
Workplace exposure limit: This substance does not have a workplace exposure limit.
PBT: This substance is not identified as a PBT substance.
Directive 1999/45/EC: This preparation meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: CRYSTALLINE SILICA 70-90%
[Xi] R37
• CALCIUM HYDROXIDE 10-30%
EINECS: 215-137-3 CAS: 1305-62-0
[Xi] R38; [Xi] R41

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of dust in the air.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Powder

Colour: Off-white

Odour: Characteristic odour

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Irritating to respiratory system. Risk of serious damage to eyes.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: Irritant.



Risk phrases: R37: Irritating to respiratory system.
R41: Risk of serious damage to eyes.

SAFETY DATA SHEET
URAGARD HT 110W - AGGREGATE COMPONENT (PART C)

Safety phrases: S22: Do not breathe dust.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S39: Wear eye / face protection.

Haz. ingredients (label): CRYSTALLINE SILICA; CALCIUM HYDROXIDE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R37: Irritating to respiratory system.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: URAGARD HT 110W - PIGMENT COMPONENT (PART D)
Company name: John L Lord & Son Ltd.
Ainsworth Road
Bury
Lancashire
BL8 2RS
United Kingdom
Tel: +44 (0)161 764 4617
Fax: +44 (0)161 763 1873
Email: derrickhulett@john-lord.co.uk

2. HAZARDS IDENTIFICATION

Workplace exposure limit: This substance does not have a workplace exposure limit.
PBT: This substance is not identified as a PBT substance.
Directive 1999/45/EC: This does not meet the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

3. COMPOSITION / INFORMATION ON INGREDIENTS

4. FIRST AID MEASURES

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes.
Ingestion: Wash out mouth with water.
Inhalation: Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.
Exposure hazards: In combustion emits toxic fumes.
Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.
Environmental precautions: Do not discharge into drains or rivers.
Clean-up procedures: Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Avoid the formation or spread of dust in the air.
Storage conditions: Store in cool, well ventilated area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Powder

Colour: Various

Odour: Odourless

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION**11. TOXICOLOGICAL INFORMATION (SYMPTOMS)**

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

12. ECOLOGICAL INFORMATION

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

PBT identification: This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.